



Product Comparison

	LOS0224T1/T2 Mini 8IGHT RTR	LOS01000 Mini 8IGHT-T RTR
Completion Level:	Ready-To-Run	Ready-To-Run
Drivetrain:	4WD	4WD
Size/Scale:	1/14	1/14
Vehicle Type:	Buggy	Truggy
Ball Bearings:	Full Bearings	Full Bearings
Batteries:	7.2V 1100mAh NiMH (LiPo optional)	7.2V 1100mAh NiMH (LiPo optional)
Charger:	Included (not sold separately)	Included (not sold separately)
Chassis:	2.5mm anodized aluminum	2.5mm Plate
Height:	4.33 in (110mm)	5 in (120mm)
Differential:	Bevel Gear	Bevel Gear
Final Drive Ratio:	9.4:1	12:01
Front Track:	8.0 in (202mm)	10.1 in (255mm)
Gear Pitch:	0.5 MOD	0.5 MOD
Ground Clearance:	.78 in (20mm)	0.9 in (23mm)
Internal Gear Ratio:	2.6:1	2.6:1
Length:	11.49 in (292mm)	13 in (319mm)
Minimum Age:	14 years	14 years
Motor or Engine:	4500Kv	4500Kv
Motor Type:	Non-Sensored Brushless	Non-Sensored Brushless
Pinion:	16T	14T
Radio:	2.4GHz DSM Technology	Spektrum DX2E DSMR
Rear Track:	8 in (203mm)	9.9 in (252mm)
Environment:	All-Terrain	All-Terrain
Shock Type:	Aluminum, threaded, oil-filled	Aluminum, threaded, oil-filled
Size/Scale:	1/14	1/14
Speed Control:	Brushless	Brushless
Spur Gear:	58T	62T
Suspension:	Independent	Independent
Tire Compound:	Soft	Soft
Tire Diameter:	1.8 in (47mm)	3.5 in (88mm)
Tire Type:	Kingpin Buggy	Blockhead
Weight:	2.15 lb (0.98 kg)	2.9 lb 1.32 kg
Wheel Diameter:	2.0 in (52mm)	2.2 in (56mm)
Wheel Type:	Dish	Dish
Wheel Width:	0.94in (24mm)	1.5 in (39mm)
Wheelbase:	7.32 in (186mm)	8.8 in (223mm)
Width:	8.03 in (204mm)	10 in (255mm)

Mini 8IGHT

Mini 8IGHT-T

